

Material

Item	Specification	Fill Capacity
High Performance DOT 3 Motor Vehicle Brake Fluid PM-1-C (US); CPM-1-C (Canada)	WSS-M6C62-A or WSS-M6C65-A1	714 ml (1.5 pt)
High Temperature Nickel Anti-Seize Lubricant XL-2	ESE-M12A4-A	—
Metal Brake Parts Cleaner PM-4-A or PM-4-B (US); CPM-4 (Canada)	—	—
Silicone Brake Caliper Grease and Dielectric Compound XG-3-A	ESE-M1C171-A	—

General Specifications

Item	Specification
Brake Disc	
Brake disc minimum thickness	17.4 mm (0.685 in)
Brake Pads	
Brake pad maximum taper wear (in any direction)	3.0 mm (0.118 in)
Brake pad minimum thickness	3.0 mm (0.118 in)

Torque Specifications

Description	Nm	lb-ft	lb-in
Anti-moan bracket U-bolt nuts	35	26	—
Bleeder screw	10	—	89
Brake caliper anchor plate bolts	103	76	—
Brake caliper flow bolt	40	30	—
Brake caliper guide pin bolts ^a	—	—	—
Brake caliper support bracket bolts	68	50	—
Brake disc shield bolts	20	—	177
Brake hose bracket bolts	15	—	133
Brake tube fitting	17	—	150

^a Refer to the procedure in this section.

