

Material

Item	Specification	Fill Capacity
MERCON® V Automatic Transmission Fluid XT-5-QM (or XT-5-QMC) (US); CXT-5-LM12 (Canada)	MERCON® V	Keep fluid level between MIN and MAX on reservoir
Premium Long-Life Grease XG-1-C or XG-1-K (US); CXG-1-C (Canada)	ESA-M1C75-B	—

Torque Specifications

Description	Nm	lb-ft	lb-in
Inner tie rod	120	89	—
LH engine mount nut	63	46	—
Power steering fluid cooler nuts	8	—	71
Power steering fluid reservoir bolt	9	—	80
Power steering line clamp plate bolt	23	17	—
Power steering pump bolts	25	18	—
Power steering pump pulley bolts (4.0L)	25	18	—
Power steering pump supply hose bracket bolt (4.0L)	8	—	71
Pressure line bracket-to-alternator stud nut (5.4L)	7	—	62
Pressure line bracket-to-A/C compressor stud nut (4.0L)	7	—	62
Pressure line bracket-to-crossmember bolt	9	—	80
Pressure line bracket-to-engine bolt (5.4L)	7	—	62
Pressure line bracket-to-pump stud nut (4.6L)	7	—	62
Pressure line bracket-to-steering gear bolt (4.6L, 5.4L)	9	—	80
Pressure line-to-pump fitting	75	55	—
Pressure line union fitting	65	48	—
Steering column coupling-to-steering gear bolt	25	18	—
Steering gear bolts	115	85	—
Tie-rod end nuts	80	59	—
Tie-rod jam nuts	55	41	—

